

Leg Extension-HM014

- |  |   |
|--|---|
| 1: Main Frame Gauge Tube 50*110*2.0mm;   | "Flat Oval Tube 50*100*2.5mm; Shroud Frame Rectangular Motion Arms Flat Oval Tube 40*80*2.0mm"                            |
| 2: Wire Spec.  | Dia 5.6mm   |
| 3: Cushion   | Material: High strength sponge, artificial PVC leather  |
| 4: Guiding Bar   | Round 20*2.0mm Stainless Steel Bar  |
| 5: Shroud Cover<br>beautiful and seamless                                      | Integrated iron guard plate makes the equipment safe,   |
| 6: Handle  | Made of TPV material, soft, non-slip and durable  |
| 7: Adjusting Position  | Pin type adjustment structure   |
| 8: Weight Stack<br>resistance; Standard configuration: 80kgx1 group, 5kg/piece | Steel plate thickness : 18mm; Better impact and wear  |
| 9: Pulleys<br>over 100,000 times non-stop fatigue tests                        | High Strength Nylon Pulleys, which have passed the  |
| 10: Accessories  | High strength bolts and locknuts, which can meet National Standard Grade 8.8, are better in strength and rust resistance. |
| 11: Size/ N.W.   | Size: 1220*1277*1601mm (L*W*H)  |
| 12: Size/ N.W.   |   |
| 13: Manual   | Chinese Manual          English Manual  |
| 14: Muscles Trained  | Exercise the quadriceps group.  |